



RXV ECO SOLVENT

High Performace Inks

RXV ink is a premium ECO solvent high density pigmented inkjet ink set formulated for use in the **Roland® SOLJET™ Pro 4 XR-640**, **SOLJET™ XF-640**, **RF-640 VERSA EXPRESS™**, and **VersaCAMM™ VSI** series printers.

Chemistry:



Eco Solvent

Available in:



EMEA



Americas & Oceania

RXV ECO SOLVENT

High Performace Inks

RXV ink is a premium ECO solvent high density pigmented inkjet ink set formulated for use in the **Roland® SOLJET™ Pro 4 XR-640, SOLJET™ XF-640, RF-640 VERSA EXPRESS™**, and **VersaCAMM™ VSI** series printers.

Triangle's **RXV** series vinyl-based ECO solvent products are optimized for high pigment density and wide color gamut. They are used on a wide range of flexible display graphics media. The formulations boast superior chemical resistance and outstanding scratch resistance. The products are intended for jetting through piezo DOD printheads at ambient temperatures and have excellent jetability consistency.

Be surprised by the RXV performances. This product will exceed your expectations providing a very low odor level, more vibrant colors and a fast drying speed. No profiling or flushing are required since this product is Color and Chemically compatible with the OEM inks.

- **Low odor**
- **Fast drying speed**
- **No profiling or flushing required**
- **Color and Chemically compatible with Roland EcoSol MAX 2 Inks**
- **Backed by INX Digital's Worldwide Ink Train Warranty for TRIANGLE® brand ink**


COLORS AVAILABLE

7 Colors



PACKAGING AVAILABLE

6 x 1 liter bottle. Net quantity 6 liters.
6 x 440ml Cartridges. Net quantity 2,64 liters.
4 x 1 liter N.bag. Net quantity 4 liters.
4 x 2 liter Eco Bulk Refill. Net quantity 8 liters.




Chemically
compatible



Color Compatible



Fast Drying Speed



Low Odor




Eco-Friendly
Packaging



Ink Train Warranty

SCAN ME



Packaging Available

Meeting our customers' needs

Our commitment is to provide the most common and used packaging's types available.
Find the package that fits your needs.



01 LITER BOTTLE



440ml CARTRIDGES



1000ml NITE BAGS



2000ml ECO REFILL

Applications

One Product, many Markets

Our products provides the best performances required by different applications and markets. Discover how many applications you could cover with this product.



BANNER



BACKLIGHT



PAPER BILLBOARDS



POS



SOFT SIGNAGE



STICKERS




CAR WRAPPING

Related Products

Improve your printer performance

Are you looking for a 440ml Chip's replacement? Do you need a permanent electronic bypass? Or are you looking for a Ink's Bulk System? In any case, INX Digital can offer the best and practical solution that fits your needs.



Chip Replacement

Roland® EcoSol MAX™, 440ml Chip Replacement, EcoSol MAX 1™, EcoSol MAX 2™, EcoSol MAX 3™

How to Purchase?

Check the availability in your region.



EMEA

Eastern Europe, Western Europe, Southern Europe,
Northern Europe, Sub-Saharan Africa, Northern Africa,
Western Asia, Southern Asia

**IMPORTANT
NOTE**

RXV cartridges are available with three different types of electronic chips.
Please, refer to the table above, to order the cartridge compatible with your ink type.

COLOR	1 Liter Bottle	1000ml Nite Bag	2000ml EcoBulk Refill	440ml EcoSol Max 1	440ml EcoSol Max 2	440ml EcoSol Max 3
Cyan	1665305-01LT	1665305-1000ML-N	1665305-2000ML-EB	1665305-440ML-ES1	1665305-440ML-RXV	1665305-440ML-ES3
Magenta	1665306-01LT	1665306-1000ML-N	1665306-2000ML-EB	1665306-440ML-ES1	1665306-440ML-RXV	1665306-440ML-ES3
Yellow	1665307-01LT	1665307-1000ML-N	1665307-2000ML-EB	1665307-440ML-ES1	1665307-440ML-RXV	1665307-440ML-ES3
Black	1665308-01LT	1665308-1000ML-N	1665308-2000ML-EB	1665308-440ML-ES1	1665308-440ML-RXV	1665308-440ML-ES3
Light Cyan	1665309-01LT	1665309-1000ML-N	1665309-2000ML-EB	1665309-440ML-ES1	1665309-440ML-RXV	1665309-440ML-ES3
Light Magenta	1665310-01LT	1665310-1000ML-N	1665310-2000ML-EB	1665310-440ML-ES1	1665310-440ML-RXV	1665310-440ML-ES3
Light Black	1478648-01LT	NOT AVAILABLE	NOT AVAILABLE	1478648-440ML-ES1	1478648-440ML-RXV	1478648-440ML-ES3
USF FLUSH	1560351-01LT	NOT AVAILABLE	NOT AVAILABLE	1560351-440ML	1560351-440ML	1560351-440ML



AMERICAS & OCEANIA

Northern America, Latin America Australia and New Zealand

COLOR	1 Liter Bottle	1000ml Nite Bag	2000ml EcoBulk Refill	440ml EcoSol Max 1	440ml EcoSol Max 2	440ml EcoSol Max 3
Cyan	1478644-01LT	NOT AVAILABLE	NOT AVAILABLE	1478644-440ML-ES1	1478644-440ML-RXV	1478644-440ML-ES3
Magenta	1478631-01LT	NOT AVAILABLE	NOT AVAILABLE	1478631-440ML-ES1	1478631-440ML-RXV	1478631-440ML-ES3
Yellow	1478643-01LT	NOT AVAILABLE	NOT AVAILABLE	1478643-440ML-ES1	1478643-440ML-RXV	1478643-440ML-ES3
Black	1478647-01LT	NOT AVAILABLE	NOT AVAILABLE	1478647-440ML-ES1	1478647-440ML-RXV	1478647-440ML-ES3
Light Cyan	1478646-01LT	NOT AVAILABLE	NOT AVAILABLE	1478646-440ML-ES1	1478646-440ML-RXV	1478646-440ML-ES3
Light Magenta	1478642-01LT	NOT AVAILABLE	NOT AVAILABLE	1478642-440ML-ES1	1478642-440ML-RXV	1478642-440ML-ES3
Light Black	1478648-01LT	NOT AVAILABLE	NOT AVAILABLE	1478648-440ML-ES1	1478648-440ML-RXV	1478648-440ML-ES3
USF FLUSH	1560351-01LT	NOT AVAILABLE	NOT AVAILABLE	1560351-440ML	1560351-440ML	1560351-440ML

TYPICAL PHYSICAL PROPERTIES

COLOR	VISCOSITY (25°C)	SURFACE TENSION (25°C)	SPECIFIC GRAVITY	LIGHTFASTNESS*
Cyan	4.3 - 5.1 mPa*s/25C	27.0 - 30.0 mN/m	950 - 990 Kg/m ³	7 - 8
Magenta	4.3 - 5.1 mPa*s/25C	27.0 - 30.0 mN/m	950 - 990 Kg/m ³	7
Yellow	4.3 - 5.1 mPa*s/25C	27.0 - 30.0 mN/m	950 - 990 Kg/m ³	6 - 7
Black	4.3 - 5.1 mPa*s/25C	27.0 - 30.0 mN/m	950 - 990 Kg/m ³	8
Light Cyan	4.3 - 5.1 mPa*s/25C	27.0 - 30.0 mN/m	950 - 990 Kg/m ³	7
Light Magenta	4.3 - 5.1 mPa*s/25C	27.0 - 30.0 mN/m	950 - 990 Kg/m ³	6 - 7
Light Black	4.3 - 5.1 mPa*s/25C	27.0 - 30.0 mN/m	950 - 990 Kg/m ³	8

FLEXIBILITY & ADHESION

RXV inks are formulated to achieve excellent adhesion to a wide variety of substrates and compatibility with wide range of banner stocks, vinyl and paper.

OUTDOOR USE

RXV inks are designed for outdoor use and, with a suitable substrate and correct ink application, should withstand 1-2 year exposure. Laboratory tests passed the 2-year outdoor durability criteria (delta E of <10 using accelerated testing equipment).

TEMPERATURE EXPOSURE & JETTING

Inks were optimized to jet in equipment operating at 25°C. Changes in ambient temperature and controlled temperature settings affect the viscosity of the ink and therefore the accuracy of drop formation and dot placement. Prolonged exposure to temperatures above 55°C should be avoided as long term exposure to high temperatures can induce pigment agglomeration.

INK STORAGE AND SHELF LIFE

These inks should be stored between 15° - 30°C (59° - 86°F). When stored properly inks have a 15 month shelf life.

RECOMMENDED FLUSH

USF - UNIVERSAL SOLVENT FLUSH - Solvent-based head wiping fluid that may be used to flush the ink train.

1560351-440ML - USF Universal Solvent Flush - 440 ml Cartridges

1560351-01LT - USF Universal Solvent Flush - 01 Liter Bottle

1560351-5LT - USF Universal Solvent Flush - 05 Liters Bottle

***These data are referring to the Blue Wool Scale**

1 = Very poor Lightfastness,

2-3 = Poor Lightfastness,

4-5 = Fair Lightfastness,

6 = Very good Lightfastness,

7-8 = Excellent Lightfastness

*Conditions apply. This information has been carefully studied from experience gained in the laboratory and under commercial situations. It is subject to change without notice. All sales are subject to our standard terms and conditions of sale. Since applications vary tremendously, the user assumes the obligation to test this product in their specific situation to determine its suitability and assumes all risk and liability related to such use. INX Digital makes no warranty, express or implied, for the use of the product for any particular application. In no event shall INX Digital be liable for damages in excess of the original cost of the product nor shall INX Digital be liable for any special or consequential damages. **Coverage was calculated using actual figures obtained from a print shop. Coverage depends on the file being printed and printer settings.



TRIANGLE®

triangleinx.com

AMERICAS & ASIA PACIFIC

150 North Martingale, Ste. 700
Schaumburg, IL 60173
+1 (630) 382-1800
info@triangleinx.com

EMEA - ITALY

Piazza Libertà, 2
21013 Gallarate VA, Italy
+39 0331 1261350
info@inxeuropa.com

EMEA - CZECH REPUBLIC

Do Certous 2621/13 - Hall I2
193 00 Prague 20 - Horni Pocernice
+420 326 374 900
info@inxeuropa.com